


**SPECIFICATION SHEET: S010**  
**SYSTEM 1600**  
**MODULAR RANGE LOCKERS**



**Dimensions:**

| Height | Width  | Depth  |
|--------|--------|--------|
| 340 mm | 300 mm | 300 mm |
| 340 mm | 380 mm | 380 mm |

**Strength and Security with Style**

|                     |                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------|
| Sturdy Construction | Door frame constructed from heavy gauge mild steel of press formed channel section.             |
| Door Strength       | Two 'five knuckle' semi-concealed hinges.                                                       |
| Style               | Attractive and functional locker design.                                                        |
| Colour              | Automated paint plant ensures consistent high quality finish in a wide range of modern colours. |

**Detailed Product Specification**

|                      |                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nesting:             | All Modular lockers are drilled in sides, tops and bottoms, to enable them to be bolted together into configurations to suit the user.                                                                                                                                                                                                                                                                                               |
| Construction:        | Spot welded and pop riveted.                                                                                                                                                                                                                                                                                                                                                                                                         |
| Material & Finish:   | Mild steel-stove enamelled (see Finish specification).                                                                                                                                                                                                                                                                                                                                                                               |
| Door Frame Assembly: | Comprising two uprights manufactured from heavy gauge mild steel of press formed channel section; top and bottom cross members which are designed to create door stops. Spot welded construction produces a rigid frame enabling door clearances to be maintained in accordance with British Standard requirements. The top cross member is provided with a series of ventilation slots.                                             |
| Doors:               | Doors are attached to the right hand side of door frame upright with two 'five knuckle' semi-concealed hinges.<br>Doors are fitted with a plastic escutcheon plate around the lock, which can also act as a name card/locker number holder.<br>The inside of the door has a full length vertical 'stiffener' to provide greater rigidity. Two rubber buffers are fitted to the top and bottom corners of the door for quiet closure. |
| Locking:             | Standard options are either 10 disc tumbler cam lock in mastered suite with two keys to each lock or, at no extra cost, a latch lock for the user's own padlock (recommended padlock shank dimensions 6 mm). Recommended padlocks are available from Total Locker Service.                                                                                                                                                           |
| Ventilation:         | Ventilation is provided by a series of unique ventilation slots in the top cross member.                                                                                                                                                                                                                                                                                                                                             |
| Paint Finish:        | Five stage automatic degreasing and phosphating process to remove surface contamination. This base gives improved adhesion and humidity resistance. The paint is applied by high-speed electrostatic rotating bells, which are computer controlled to ensure the correct thickness of paint is applied. The component parts are then stove enamelled at the correct temperature to ensure a hard paint finish is achieved.           |
| Colour Range:        | Standard locker frame stove enamelled colours is: "Ice". Standard door stove enamelled colours are: "Ice", "Rockpool", "Smoke", "Nimbus", "Forest", "Skye", "Kingfisher", "Royale", "Cherry"                                                                                                                                                                                                                                         |

|                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>OPTIONAL EXTRAS:</b> | The following can be supplied at an additional cost and, if included, will be specified in the quotation.                                                                                                                                                                                                                                                                                                                                                                                                       |
| Shelf:                  | Shelf fitted at 195 mm height from the bottom of unit. Front edge has a 20 mm safety edge flange.                                                                                                                                                                                                                                                                                                                                                                                                               |
| Combination Lock:       | The standard cam lock or latch lock can be replaced with a door-mounted combination lock with master key over-ride facility and user codes which can be reset.                                                                                                                                                                                                                                                                                                                                                  |
| Perforation:            | Most parts of the locker can be perforated with the unique perforation profile (please refer to Information Sheet I008).                                                                                                                                                                                                                                                                                                                                                                                        |
| Locker Numbering:       | <ul style="list-style-type: none"> <li>a) Number Label – Made of transparent vinyl, with a permanent, self-adhesive back. Numbers are printed in black and can comprise one to four digits.</li> <li>b) Number Plate – Made of laminated plastic, white numbers on black, numbers can comprise one to four digits.</li> <li>c) Number Discs – Laminated plastic 25 mm diameter, white numbers on black, numbers can comprise one to four digits. The disc is holed and a split key ring is provided.</li> </ul> |
| Plinths:                | A special 50 mm high plinth is available to raise a Modular locker from the ground.                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Stands:                 | <p>Groups of Modular lockers can be mounted on 760 mm high stands. The stands are constructed from 25 mm square section mild steel tube and finished as for the Modulares.</p> <p>For the 300 mm unit the stand is 1500 mm wide x 300 mm deep and will accommodate 5 Modular units wide. We recommend no more than 4 units high.</p> <p>For the 380 mm unit the stand is 1520 mm wide x 300 mm deep and will accommodate 4 Modular units. We recommend no more than 4 units high.</p>                           |
| Installation:           | We offer a full installation service for its products.                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

**After Sales Service:** All of our products are supported by our Service Department who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment.

- **Health & Safety:** Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.